



LUFDBKEL - Digital Feedback Eliminator
MAT #408184265

Technical Specifications

Audio Memory:	4 minutes
Recording Capacity:	Up to 16 pages, with maximum 1-minute length per message
Number of Plays:	Play each message 1 or 2 times
Delay Between Plays:	1, 3, 5, or 10 seconds
Page Audio Input:	Transformer-isolated 600-ohm line input with -20 dBm to +4 dBm (nominal 0 dB) input level
Priority Audio Input:	Transformer-isolated 600-ohm, with -20 dBm to +4 dBm (nominal 0 dBm) input level
Audio Line Output:	Transformer-isolated 600-ohm line-level, +4 dBm max. continuously adjustable
Audio Power Output:	Transformer-isolated 8-ohm low impedance, limited to approx. 0.5 watts into 8 ohms (adjustable)
Relay Contacts:	1 Amp, 24V DC noninductive loads
Power Requirements:	24V DC, 500 mA
Frequency Response:	6.8 kHz, and 60 dB of dynamic range
Operating Temperature:	0 to +40°C (+32 to 104°F), relative humidity from 0 to 85%, non-condensing, and at altitudes up to 10,000 feet above sea level
Dimensions:	10" W x 1.5" H x 6.5" D
Product Weight:	5 lb.